



## Multi Products Company Plunger Lift Equipment

### Modular Sub Surface Spring Specifications

The Multi Products Company 2 1/2" Modular Sub Surface Spring:

Overall Length	20" OAL to 26" OAL
Total Weight	9 lbs. To 14 lbs.
Fish Neck size	1 3/8" to 1 3/4" by 2 5/8" OAL to shoulder.
Attachment	Threaded and pinned directly to Sliding Stem through spring.
Material	4140 Fish head to 1220 for Collett.
Base Length	6 1/2" OAL w/ 2 3" x 1/2" slots opposing at 180°.
Base Thread	12 UN Thread.
Base Diameter	2 3/16" OD X 1 3/4" ID.
Collett Material	1220 Steel with 6 prongs cut 2" long with interior cut latch for attaching to Fishing head.
Center Rod material	4140 Steel threaded and pinned with nut to lower end to attach Base.
Spring Material	Either Heat Treated CS wire with Stainless Steel Option.
Color	Exterior of body and spring is red. All options are also red.
Available Options	Free Standing No Go for sitting on Seating Device. Latch down Option for either 1 3/8" or 1 3/4" fish head to latch on a tubing Stop or Collar stop. Cup Seat Standing Valve Option with seat and Ball to stop reverse flow . From the bottom of the tubing. Ball can be removed to allow for seat Cups to work as an anchor. H2S Modular Springs are available.



Customer Inquiries and Service should be directed to: Multi Products Company .  
service@plungerlift.com  
Tel. 330-674-5981  
Fax 330-674-2125

