



# MULTI-SEAL BAR STOCK PLUNGER

Endurance Lift's Multi-Seal bar plungers are optimal for wells having drifted and broached tubing or as a utility plunger for wells with solids. Wells coming off continuous flow or coming off a long shut-in time are also candidates for a Multi-Seal plunger.

Solidly built with a single piece of 4140 machined steel and no moving parts, Endurance uses a unique velocity seal to lift fluids. Maximum operating efficiency is achieved because the plungers are machined to the tolerance and drift specifications of the tubing. Shorter and lighter versions are available for specific plunger lift system requirements.

## FEATURES

- Single piece 4140 machined steel
- Unique velocity seal for fluid lift
- No moving parts
- Rifled sections allow for even wear on plunger surface

## BENEFITS

- Low cost
- Versatility makes it suitable for multiple well conditions
- Reduces operating expense for the life of the well

## Technical Specifications

Fall Rate (Ft/Min)	350 - 400
Size	2 - 3/8 in.
Length	12 in.
Plunger O.D.	1.875 - 1.900 in.
Fishing Neck Size	1 - 3/8 in.
Weight	8 lbs

For more information about Endurance Lift's plungers, lift systems and wellhead equipment, contact your local representative or email [service@plungerlift.com](mailto:service@plungerlift.com).

**RUN LONGER. PRODUCE MORE.**

[www.endurancelift.com](http://www.endurancelift.com)



**ENDURANCE**  
LIFT SOLUTIONS