

SALES CONTACTS

 Western U.S. (970) 433-4335
 Southern U.S. (940) 393-2894
 Eastern U.S. (724) 549-1729

STEADY-FLO SP™

PLUNGER

Endurance Lift's Steady-Flo SP (Padded Steady-Flo) is a good choice for wells with erratic fluid production that need extra sealing capacity offered by a pad design. The Steady-Flo SP works on the same principle of slipping fluid as our original Steady-Flo design, that lowers fall speeds, but also uses our ConformaSeal pad which helps to increase sealing capacity. The result is a plunger that achieves effective deliquification in low energy wells, reduces shut-in time and evens out fluid production – providing multiple benefits over a standard dual pad plunger design.

FEATURES

- ConformaSeal pad
- Wear indicators on pad
- Dual choke design
- Three choke sizes
- Available in 4140 steel or 17-4 stainless

BENEFITS

- Extra sealing capacity
- Reduces shut-in time
- Evens out fluid production



Dual choke design that slips fluid during plunger cycles to even out fluid production.

Technical Specifications

Varying Choke sizes: #10, #16 or #20

Fall Rate (Ft/Min)	#10 (250 - 300), #16 (300 - 350), #20 (350 - 400)
Size	2 - 3/8 in.
Length	15 1/8 in.
Plunger O.D.	1.885 in. body – 2.050 in. pads
Fishing Neck Size	1 - 3/8 in.
Weight	8.4 lbs

For more information about Endurance Lift's plungers, lift systems and wellhead equipment, contact your local representative or email service@plungerlift.com.

RUN LONGER. PRODUCE MORE.

www.endurancelift.com



ENDURANCE
LIFT SOLUTIONS