

SKIRTED PAD PLUNGER

The Skirted Pad Plungers utilized interlocking pads to achieve maximum sealing efficiency when lifting liquids. The pad are offset to prevent any fluid slipping past one pad set seam from slipping past the next one. Dual pad springs keep the pad balanced in the assembly. Wear indicators allow for easy monitoring and scheduling of replacement.

The pad design is such that as the plunger wears, it will not wear out the plunger body allowing the pads to fall out.

FEATURES

- Three pads per set allow for maximum sealing against tubing wall
- 60° pad offset prevents slippage past pads
- Long chamfers on pads allow for easy passage through gate valves and tight spots
- No pinned threaded connections

BENEFITS

- Long plunger lift
- Efficient sealing reduces the number of cycles needed per day.
- Reduces operating expenses over the life of the well
- Wear indicators for easy inspection.

Technical Specifications

Fall Rate (Ft/Min)	300-400 ft/min
Size	2-3/8 in
Length	12.58 in
Plunger O.D.	1.860 in
Fishing Neck Size	1-3/8
Weight	8.2 lbs

For more information about Endurance Lift's plungers, lift systems and wellhead equipment, contact your local representative or email service@plungerlift.com.

RUN LONGER. PRODUCE MORE.

www.endurancelift.com



ENDURANCE
LIFT SOLUTIONS